V A L V E S

In-Line Flow Control Valves



FEATURES:

- Carbon steel body
- Designed to provide precision flow control & shut off in one flow direction & provide free flow in the opposite direction
- Color bands allow fast return to a previous setting
- Set screw locks valve to any setting
- Operating temp range -20°F through 210°F

Model In-Line Flow Control Valves

MODEL No.	PORT SIZE	MAX PSI	MAX FLOW	SHIPPING WEIGHT	LIST PRICE
WFC-400	¼" NPTF	5,000 PSI	5 GPM	0.5	35.74
WFC-600	⅜" NPTF	5,000 PSI	8 GPM	0.9	38.45
WFC-800	½" NPTF	5,000 PSI	15 GPM	1.5	47.65
WFC-1200	¾" NPTF	3,000 PSI	25 GPM	2.5	92.60
WFC-1600	1" NPTF	3,000 PSI	40 GPM	3.5	225.26

MODEL NO.	MAX FLOW	A	B	C	D	E	F	G	H
WFC-400	5 GPM	¼ NPTF	1.79	1.59	2.62	1.66	.81	.41	.811
WFC-600	8 GPM	⅜ NPTF	2.18	1.94	2.75	1.75	1	.5	1
WFC-800	15 GPM	½ NPTF	2.70	2.42	3.44	2.23	1.25	.63	1.19
WFC-1200	25 GPM	¾ NPTF	3.38	2.81	3.88	2.58	1.5	.75	1.38
WFC-1600	40 GPM	1 NPTF	4.87	4.21	5	3.22	1.75	.88	1.88



